MAINTENANCE-FREE

75 AMP/HR BATTERY AGM SEALED LEAD-ACID BATTERY



- Flame arresting, oneway pressure relief vent for safety and long life
- Multi-cell design for economy of installation and maintenance
- Thermally welded case-to-cover body to eliminate leakage
- Can be used in any orientation: upright, side or end mounting recommended


- Maximum plate thickness to support frequent deep discharge cvcles
- Computer generated grid design optimized for high power density
- Low-calcium grid alloy for reduced gas emission and ease of recycling
- Manufactured by an IS09001 certified facility
- AGM Design and ULrecognized component

BEWARE OF OTHER BATTERIES WHICH

Certified manufacturer using #1 Lead Ingot (99.994% pure) which eliminates impurities such as iron, copper, and silver that cause increased self-discharge. Third Party verified purity with each production run.

RICHTECH 75 AMP SEALED LEAD BATTERY PERFORMANCE*

*Based on 75 amp/hr SLA battery, 10' of lift, 10 second cycle



If Backup Pump Cycles Every . . .

166 HOURS **5 MINUTES** 2 MINUTES 66 HOURS 1 MINIITE 33 HOURS 5.5 HOURS CONSTANTLY-

PitBoss system automatically recharges battery when power is restored.

6

CFIIS **PER UNIT** **VOLTAGE PER UNIT**

12

50.7 lbs 23kg

WFIGHT

ELECTROLYTE

Absorbed

H₂SO₄

SG = 1.30

350 Amps

MAX DISCHARGE CURRENT

1050 Amps @0.1 sec.

SHORT CIRCUIT CURRENT

 $8 \text{ m}\Omega$

OHMS IMPED 60 HZ

RICHTECH

800.677.7791 RICHTECHINDUSTRIES.COM